




ECO PHYSICS nCLD AL

APPLICATION EXAMPLES

- Ambient air monitoring
- Outdoor and indoor application
- Certification and calibration
- Research



The nCLD AL is the next generation in single-channel ambient air monitoring instrumentation. Unique in speed and precision, the nCLD AL is modular designed and capable of sequentially measuring NO, NO₂ and NO_x. Its graphical user interface also individually displays and connects to other instrument's data.

Measurement of:

- NO
- NO₂
- NO_x

Flexible Ambient Air Monitoring

The nCLD AL is the ideal instrument for ambient air monitoring, either installed in racks, fixed monitoring stations or mobile laboratories. Besides the ambient air in the open environment, the analyzer is also suitable for air quality monitoring in production plants and offices (TLV = threshold limit value). The nCLD AL is a one-channel NO_x-detector based on a modular principle. The measurement ranges are individually adjustable, the parameters are NO, NO₂ and NO_x and the instrument's inlet operates at ambient pressure. The calibration sequence runs quick and automatic while all necessary data is continuously stored and readily available anywhere and at any time.

User Friendliness

The new touch sensitive graphical user interface enables the user to individually adjust the instrument operation and data management according to his/ her needs and applications. The bright 7" monitor gives a clear overview and allows numerical and graphical display of values. Multiple digital in- and outputs guarantee a maximal connectivity and flexibility for the remote operation, control and maintenance of the nCLD AL, ensuring unsurpassed precision and reliability.

Compact, Modular and Intelligent!

The nCLD AL is manufactured in a new compact and modular layout, in which each essential component of the chemiluminescence analyzer hosts its own CPU and interacts with other CPUs by BUS-communication. This assembly increases accessibility and serviceability by reducing wiring and piping. The measurement principle will conform to the standard method for NO_x-detection in ambient air (EN 14211).

- Rapid system integration and rack mounting
- Compact and modular design
- Virtually maintenance free even in continuous operation
- Four freely selectable measuring ranges

Graphical user interface for individual analyzer operation and data management

Analyzer	
NO	461.0 ppb
NOx	981.0 ppb
NO2	520.0 ppb

Measurably better

SPECIFICATIONS


nCLD AL

Analyzer type	single channel CLD with cooled PMT for sequential measurement of NO, NO ₂ , NO _x	Power required	350 VA (incl. membrane pump and ozone scrubber)
Measuring ranges	four freely selectable ranges from 100 ppb - 50'000 ppb	Supply voltage	110 V / 230 V/50 - 60 Hz
Min. detectable concentration*	0.4 ppb (single-channel mode)	Interface	USB(3x), HDMI, Bluetooth, RS232 (w/o 9pin connector), LAN, WLAN
Noise at zero point (1σ)*	<0.2 ppb (single-channel mode)	Dimensions	height: 133 mm (5¼ ") width: 450 mm (19 ") with molding: 495 mm depth: 540 mm (21.2 ")
Lag time	30 sec (min. toggle interval)	Weight	23 kg (51 lb)
Rise time (0 - 90%)	<1 sec (single-channel mode)	Delivery includes	nCLD AL analyzer, power cable, FTDI-RS232-USB cable, USB-LAN adapter
Temperature range	0 - 40 °C (non-freezing)	Standard	nCLD AL · Y - molybdenum converter · External pump · External power supply
Humidity tolerance	5 - 95% rel. h (non-condensing, ambient air and sample gas)	Options	· USB-RS232 9pin connector · toggle mode for NO ₂ measurement Analog output (External Box) · 0 - 10 V · 4 - 20 mA into 500 Ω max.
Sample flow rate	1.0 l/min		
Input pressure	600 - 1200 mbar abs.		
Dry air use for O ₃ generator	internally generated (no external supply gas required)		

© ECO PHYSICS AG, Switzerland 2020 - 1/2

FLOW DIAGRAM

*Depending on filter setting
Connectivity properties are country-specific
ECO PHYSICS reserves the right to change these specifications without notice.



ECO PHYSICS

ECO PHYSICS AG · POB · CH-8635 DUERNTEN · TEL. +41 55 220 22 22 · E-MAIL INFO@ECOPHYSICS.COM

WWW.ECOPHYSICS.COM