

POLI MP400P Portable Gas Detector

Document Ref: SL-044 V2




Portable Gas Detector

POLI MP400P Monitor

- ▶ **Wide Selection of Plug-and-Play Smart Sensors**
(Carry Calibration Data)
- ▶ **16-Hour Rechargeable Li-ion Battery**
USB Micro Charger & Communications cable
- ▶ **Pump-Off Switch and Low-Power Sensor Options**
- ▶ **Automatic Flow Fault on Pump**
- ▶ **360° LED Alarm Bar and Man-Down Alarm**
- ▶ **6 Month Continuous Datalogging**
- ▶ **Durable Double Shot Outer Case**
- ▶ **Wireless Remote Team Communication Available**
(See mSquad & mPlatoon Datasheets)
- ▶ **Mobile App**
For POLI Simulation and Training



 internationalgasdetectors.com

 +44 (0)161 483 1415

 sales@internationalgasdetectors.com

 /international-gas-detectors-ltd

Triton House, Crosby Street
Stockport, SK2 6SH



Portable Gas Detector

POLI MP400P

The POLI multi-gas meters offer monitoring of 4 or 5 toxic gases, oxygen (O₂), combustibles (LEL), carbon dioxide (CO₂) and volatile organic compounds (VOCs). An advanced model with built-in pump with a wide selection of sensors available for a wide range of applications.

Smart sensors carry calibration and ID information with them for quick exchange in the field during Hazmat response.

Specific sensors include:

- electrochemical (EC) for carbon monoxide (CO),
- hydrogen sulphide (H₂S),
- ammonia (NH₃),
- hydrogen cyanide (HCN),
- hydrogen chloride (HCl),
- hydrogen fluoride (HF),
- chlorine (Cl₂),
- chlorine dioxide (ClO₂),
- nitric oxide (NO),
- nitrogen dioxide (NO₂),
- sulphur dioxide (SO₂),
- ethylene oxide,
- methyl mercaptan,
- and others.

Also available are pellistors for

- LEL level combustibles,
- non-dispersive infrared (NDIR) for Vol% level CO₂ or hydrocarbons,
- and photo-ionization detector (PID) for ppm level VOCs.

Use of combination CO/H₂S or SO₂/H₂S sensors allow up to 5 gas measurements in a single instrument.


The MP400P has rugged construction and easy-to-learn 2-button operation. The unique Man-Down alarm feature notifies team workers wirelessly if a user becomes incapacitated.



Portable Gas Detector

Mobile App

Scan the QR code to download the POLI Training App, this simulates all the functions and alarms of an actual POLI monitor.



Sensor Options

Sensor	Range	Resolution
PID	0-200 PPM 0-2000 PPM 0-10000 PPM	0-01 PPM 0.1 PPM 1 PPM
Oxygen (O2) Lead Wool	0-30% VOL	0.1% VOL
Lead-Free	0-30% VOL	0.1% VOL
Combustibles (LEL%)	0-100% LEL	1% LEL
Hydrocarbons (Vol%)	0-100% VOL	0.1% VOL
Dual-Range LEL% / VOL %	0-100% VOL	1% LEL
Carbon Dioxide (CO2)	0-50000 PPM	100 PPM
Carbon Monoxide (CO)	0-1000 PPM	1 PPM
Hydrogen Sulphide (H2S)	0-100 PPM 0-1000 PPM	0.1 PPM 1 PPM
CO + H2S	0-500 PPM 0-200 PPM	1 PPM 0.1 PPM
SO2 + H2S	0-20 PPM 0-100 PPM	0.1 PPM 0.1 PPM
Ammonia (NH3)	0-100 PPM 0-500 PPM	1 PPM 1 PPM
Chlorine (CL2)	0-50 PPM	0.1 PPM

Chlorine Dioxide (CLO2)	0-1 PPM	0.01 PPM
Phosgene (COCL2)	0-1 PPM	0.01 PPM
Hydrogen (H2)	0-1000 PPM	1 PPM
Hydrogen Chloride (HCL)	0-15 PPM	0.1 PPM
Hydrogen Fluoride (HF)	0-20 PPM	0.1 PPM
Hydrogen Cyanide (HCN)	0-100 PPM	0.1 PPM
Nitric Oxide (NO)	0-250 PPM	1 PPM
Nitrous Oxide (N2O)	10-1000 PPM	10 PPM
Nitrogen Dioxide (NO2)	0-20 PPM	0.1 PPM
Phosphine (PH3)	0-20 PPM 0-1000 PPM	0.01 PPM 1 PPM
Sulphur Dioxide (SO2)	0-20 PPM 0-100 PPM	0.1 PPM 0.1 PPM
Acetaldehyde (C2H4O)	0-20 PPM	0.1 PPM
Ethylene Oxide (ETO)	0-100 PPM	0.1 PPM
Methyl Mercaptan (CH3SH)	0-10 PPM	0.1 PPM
Tetrahydrothiophene (THT)	0-40 PPM	0.1 PPM

Order Codes

#	Gas	Range	Pump	Note
0	Empty	-	-	-
1	PID	200 PPM	Required	-
2	PID	2000 PPM	Required	-
3	CO2	50.000 PPM	-	Low Power
4	CO2	15.000 PPM	-	-
5	VOL Hydrocarbons	100% LEL CH4	-	-
6	LEL/VOL Dual Range CH4	100% LEL 100% VOL CH4	-	-
7	LEL Hydrocarbons	100% LEL CH4	-	-
8	LEL Hydrocarbons	100% LEL CH4	-	-
9	LEL Combustible Pellistor	100% LEL	-	-
A	LEL Combustible Pellistor	100% LEL	-	Low Power
B	O2	30% VOL	-	-
C	O2	30% VOL	-	-
D	H2S	100 PPM	-	-
E	H2S	1000 PPM	-	-
F	CO	1000 PPM	-	-
G	CO	1000 PPM	-	Low H2 cross sensitivity
H	SO2	20 PPM	-	-

I	SO2	100 PPM	-	-
J	NO	250 PPM	-	-
K	NO2	20 PPM	Preferred	-
L	CL2	50 PPM	Preferred	-
M	HCN	100 PPM	Preferred	-
N	NH3	100 PPM	Preferred	-
O	NH3	500 PPM	Preferred	-
P	PH3	20 PPM	-	-
Q	PH3	1000 PPM	-	-
R	CLO2	1 PPM	Required	-
S	HCL	15 PPM	Required	-
T	HF	20 PPM	Required	-
U	CH3SH	20 PPM	-	-
V	H2	1000 PPM	-	-
W	CO + H2S	500 PPM - 200 PPM	-	-
X	H2S + SO2	100 - 20 PPM	-	-
Y	C2H4O	20 PPM	Preferred	-
Z	ETO	100 PPM	Preferred	-
&	N2O	1000 PPM	Required	Training video provided

Specifications

Size	5.74 x 3.31 x 1.65 in (140 x 84 x 42 mm)
Weight	15.5 oz (435g)
Sensor	Over 30 interchangeable and field-replaceable sensors including PID for VOCs, EC for Toxic and O ₂ , Pellistor for LEL, and NDIR for LEL, Vol% & CO ₂
Response Time	15 seconds (LEL/CO/H ₂ S/O ₂) Others vary—see sensor specification sheet
Battery	Rechargeable Li-ion pack: 16 hours in diffusion mode, 12 hours with pump
Direct Readout	Real-time reading of gas concentration PID measurement gas and correction factor Visual compliance indicator Battery status Datalogging on/off STEL, TWA, peak and minimum values Man-Down alarm on/off
Display	128 x 128 graphical LCD, 1.77 x 1.73 in (45 x 44mm), LED backlight for enhanced readability Automatic screen “flip” feature
Keypad	2 Operation keys
Sampling	Built-in pump or diffusion
Calibration	Manual calibration or automated using POLI Docking Box. CaliCase option allows automatic bump test and calibration on up to 4 units simultaneously
Alarms	Audible (95dB @ 30 cm) Visual (flashing bright red LEDs) Vibration On-screen indication of alarm conditions Man-Down alarm with pre-alarm Panic Alarm (manual)
Datalogging	Continuous datalogging (6 months for 4 sensors at 1-minute intervals, 24 hours/day and 7 days/week)
Charging and Communication	Charging, data download, instrument setup and firmware upgrades on PC or laptop via PC comms, cradle, travel charger, or CaliCase
Temperature	4° to 122°F (-20° to 50°C)
Humidity	0% to 95% Relative humidity (non-condensing)
IR Rating	IP-65 (pump versions); IP-67 (diffusion versions)
Safety Certification	Class I, Div 1, Group ABCD T4, -20°C ≤ T _{AMB} ≤ +50°C Ex ia IIC T4 Ga II 1G Ex ia IIC T4 Ga European Conformity
EMI/RFI	EMC Directive: 2014/30/EU
Warranty	2 Years on instruments 2 Years on sensors for LEL, LEL/Vol, O ₂ , CO, CO ₂ , H ₂ S, SO ₂ , HCN, NO, NO ₂ , PH ₃

*Due to ongoing research and product improvement, specifications are subject to change without notice